


SoliTek is a European manufacturer of top quality PV cells and modules with headquarters and production plant in Vilnius, Lithuania.

The company combines the most sophisticated technologies and 20 years of experience.



20

years product
guarantee

25

84,8% max
output guarantee

SoliTek Standard HC.120-W-370

Standard 120 half-cut cell module with white backsheet


Working conditions	1500
Maximum system voltage	DC 1500 V (TUV)
Operating temperature	-40°C / +85°C
Maximum reverse current	20 A
Maximum wind /snow load	3800/5400Pa
IP protection level	68
Safety class	II

Temperature coefficients	
Current temperature coefficient (α)	+0,049% /° C
Voltage temperature coefficient (β)	-0,33% /° C
Power temperature coefficient (δ)	-0,36% /° C
Nominal Operating Module Temperature	43±2°C

Electrical parametres		Unit	Value
Parameter			
Maximum power*	Pmax	W	370
Maximum power point voltage	Vmpp	V	34,1
Maximum power current	Impp	A	10,85
Open circuit voltage	Voc	V	41,4
Short circuit current	Isc	A	11,41
Efficiency	η	%	20,00

*Under Standart Test Conditions (STC) of irradiance of 1000W/sq. m., spectrum AM 1.5 and cell temperature of 25 °C

Mechanical data	
Cell size (mm)	166x83
Number of cells	120 (6x20)
Front side glass	3,2 mm
Weight	20 kg
Dimensions (L x W x H)	1765x1048x35
J-box	IP68
Cable length	400mm (or customized length)
Cable cross section size	4 mm ²
Number of diodes	3
Plug-in connection	MC4 compatible
Frame	Black anodized aluminium frame



A: Drainage; B: Ventilation; C: Mounting holes; D: Earthing;